

The `color` package*

D. P. Carlisle

2005/11/14

1 Introduction

This package implements L^AT_EX support for colour, for those dvi drivers that can produce coloured text.

The user level documentation of this package is contained in the document *Packages in the ‘graphics’ bundle* in the file `grfguide.tex`.

2 Options

1 `\package`

First we save the catcodes of some characters, and set them to fixed values whilst this file is being read.

```
2 \edef\Gin@codes{%
3   \catcode'\noexpand\^^A\the\catcode'\^^A\relax
4   \catcode'\noexpand\" \the\catcode\" \relax
5   \catcode'\noexpand*\the\catcode\'*\relax
6   \catcode'\noexpand!\the\catcode\'!\relax
7   \catcode'\noexpand\:\the\catcode\':\relax}
8 \catcode'\^^A=\catcode\'%
9 \catcode\'\"=12
10 \catcode\'*=11
11 \catcode\'!=12
12 \catcode\':=12
```

`\Gin@driver` Initialise the macro to hold the driver file name.

```
13 \providecommand\Gin@driver{}
```

`\color@error` Helper macro for error handling (redefined by the monochrome option to make errors warnings).

```
14 \def\color@error#1{%
15   \@latex@error{Undefined color #1}\@ehd}
```

`\ds@monochrome` The monochrome option should be used *in addition* to one of the standard driver options.

```
16 \DeclareOption{monochrome}{%
17   \def\color@error#1{\PackageInfo{color}{Undefined color #1}}%
18   \AtEndOfPackage{%
```

*This file has version number v1.0j, last revised 2005/11/14.

```

19 \colors@false
20 \def\set@color{%
21   \c@lor@special\m@ne
22   {color push \current@color}\aftergroup\reset@color}%
23 \def\reset@color{\c@lor@special\m@ne{color pop}}%
24 \def\set@page@color{%
25   \c@lor@special\m@ne{background \current@color}}%
26 \def\define@color#1#2{%
27   \c@lor@special\m@ne{define #1 #2}}}}

```

`\ds@debugshow` The `debugshow` option turns on debugging info (perhaps).

```

28 \DeclareOption{debugshow}{\catcode'\^A=9 \let\GDebug\typeout}

```

Now the options for supported drivers.

`\ds@dvips` Tom Rokicki's dvips driver, and the X Windows previer, xdvi which uses (a subset of) the same `\specials`.

```

29 \DeclareOption{dvips}{\def\Gin@driver{dvips.def}%
30   \def\c@lor@namefile{dvipsnam.def}}
31 \DeclareOption{xdvi}{\ExecuteOptions{dvips,monochrome}}

```

`\ds@dvipdf` Sergey Lesenko's dvipdf driver.

```

32 \DeclareOption{dvipdf}{\def\Gin@driver{dvipdf.def}}

```

`\ds@dvipdfm` Mark Wick's dvipdfm driver.

```

33 \DeclareOption{dvipdfm}{\def\Gin@driver{dvipdfm.def}}

```

`\ds@dvipdfmx` The driver for the dvipdfmx project.

```

34 \DeclareOption{dvipdfmx}{\def\Gin@driver{dvipdfmx.def}}

```

`\ds@pdftex` Han The Thanh's T_EX variant.

```

35 \DeclareOption{pdftex}{\def\Gin@driver{pdftex.def}}

```

`\ds@xetex` Jonathan Kew's T_EX variant.

```

36 \DeclareOption{xetex}{\def\Gin@driver{xetex.def}}

```

`\ds@dvi` The drivers of the Y&Y T_EX system. (Which use the same `\specials`).

```

37 \DeclareOption{dvipsone}{\def\Gin@driver{dvipsone.def}}
38 \DeclareOption{dviwindo}{\ExecuteOptions{dvipsone}}

```

`\ds@emtex` Freely available drivers for PCs.

```

39 \DeclareOption{emtex}{\def\Gin@driver{emtex.def}}
40 \DeclareOption{dviwin}{\def\Gin@driver{dviwin.def}}

```

`\ds@oztex` The OzT_EX system for a Macintosh. Since release 3 of OzT_EX, merge with dvips back end.

```

41 \DeclareOption{oztex}{\ExecuteOptions{dvips}}

```

`\ds@textures` Blue sky's Textures system on a Macintosh.

```

42 \DeclareOption{textures}{\def\Gin@driver{textures.def}}

```

<code>\ds@pctexps</code>	The drivers for PTI's T _E X system on PCs.
<code>\ds@pctexwin</code>	43 <code>\DeclareOption{pctexps}{\def\Gin@driver{pctexps.def}}</code>
<code>\ds@pctexhp</code>	44 <code>\DeclareOption{pctexwin}{\def\Gin@driver{pctexwin.def}}</code>
<code>\ds@pctex32</code>	45 <code>\DeclareOption{pctexhp}{\def\Gin@driver{pctexhp.def}}</code> 46 <code>\DeclareOption{pctex32}{\def\Gin@driver{pctex32.def}}</code>
<code>\ds@truetetex</code>	The drivers of the Kinch T _E X system on PCs, and its version with extra <code>\special</code>
<code>\ds@tcidvi</code>	handling dll's as shipped with TCI's Scientific Word. 47 <code>\DeclareOption{truetetex}{\def\Gin@driver{truetetex.def}}</code> 48 <code>\DeclareOption{tcidvi}{\def\Gin@driver{tcidvi.def}}</code>
<code>\ds@vtex</code>	V _T _E X driver. 49 <code>\DeclareOption{vtex}{\def\Gin@driver{vtex.def}}</code>
<code>\ds@dvi2ps</code>	Old, probably obsolete, drivers commented out. See the section on 'Driver support'
<code>\ds@dviaw</code>	in grfguide to see how to re-enable these options in <code>color.cfg</code> if you need them.
<code>\ds@dvilaser</code>	50 <code>%\DeclareOption{dvi2ps}{\def\Gin@driver{dvi2ps.def}}</code>
<code>\ds@dvitops</code>	51 <code>%\DeclareOption{dviaw}{\def\Gin@driver{dviaw.def}}</code>
<code>\ds@psprint</code>	52 <code>%\DeclareOption{dvilaser}{\def\Gin@driver{dvilaser.def}}</code>
<code>\ds@pubps</code>	53 <code>%\DeclareOption{dvitops}{\def\Gin@driver{dvitops.def}}</code>
<code>\ds@ln</code>	54 <code>%\DeclareOption{psprint}{\def\Gin@driver{psprint.def}}</code> 55 <code>%\DeclareOption{pubps}{\def\Gin@driver{pubps.def}}</code> 56 <code>%\DeclareOption{ln}{\def\Gin@driver{ln.def}}</code>
<code>\ds@dvipsnames</code>	By default the named colour model has no pre-declared names. The <code>dvipsnames</code>
<code>\ds@nodvipsnames</code>	option predeclares all the names in the colour prologue of dvips. The <code>dvips</code> option automatically implies <code>dvipsnames</code> unless this choice is overruled with the <code>nodvipsnames</code> option. For other drivers, eg <code>textures</code> you may use this option to explicitly request that these names be declared. 57 <code>\DeclareOption{dvipsnames}{\def\c@lor@namefile{dvipsnam.def}}</code> 58 <code>\DeclareOption{nodvipsnames}{\let\c@lor@namefile\relax}</code>
<code>\ds@usenames</code>	The <code>usenames</code> option modifies the behaviour of <code>\DefineNamedColor</code> So that it declares the same name as a "user's colour" for use in a <code>\color</code> command, as well as a name in the <code>named</code> colour model. The normal behaviour is just to declare the name in the named colour model. 59 <code>\let\c@lor@username\@gobble</code> 60 <code>\DeclareOption{usenames}{%</code> 61 <code>\def\c@lor@username#1{%</code> 62 <code>\expandafter\color@named\csname\string\color @#1\endcsname{#1}}</code>

3 Using Colours

3.1 Declarative form

`\color` `\color{declared-colour}` switches to the colour *declared-colour*, which must previously have been defined using `\definecolor`. This colour will stay in effect until the end of the current T_EX group.

`\color[model]{colour-specification}` is similar to the above, but uses a colour not declared by `\definecolor`. The allowed *model*'s vary depending on the driver. The syntax of the *colour-specification* argument depends on the model.

```

63 \DeclareRobustCommand\color{%
64   \ifnextchar[\@undeclaredcolor\@declaredcolor}

\@undeclaredcolor Call the driver-dependent command \color@{model} to define \current@color,
then call \set@color to change the current colour accordingly.
65 \def\@undeclaredcolor[#1]#2{%
66   \ifundefined{color@#1}%
67     {\c@lor@error{model '1'}}%
68     {\csname color@#1\endcsname\current@color{#2}%
69       \set@color}%
70   \ignorespaces}

\@declaredcolor \let \current@color to the internal representation of the colour if the colour
has been declared, otherwise generate an error. Finally call \set@color to effect
the colour change.
71 \def\@declaredcolor#1{%
72   \ifundefined{\string\color @#1}%
73     {\c@lor@error{'1'}}%
74     {\expandafter\let\expandafter\current@color
75       \csname\string\color @#1\endcsname
76       \set@color}%
77   \ignorespaces}

```

3.2 Command (Argument) Form

`\textcolor` `\textcolor{declared-colour}{text}` and `\textcolor[model]{colour-spec}{text}` are just alternative syntax for `\color`, in which the groups are added implicitly. Thus *text* appears in the specified colour, but then the colour reverts to its previous value. The naming is by analogy with `\textrm` (as opposed to `\rm` and `\rmfamily`) although it is slightly a misnomer as the command also works in math-mode.

Since December 95, in fact this command has one other difference from `\color`. It calls `\leavevmode` to ensure the start of horizontal mode. Specifically this means that a construction such as

```
xxx\parbox[t]{1cm}{\textcolor{red}{a}}....
```

now works as expected, with the `xxx` and the red `a` lining up correctly.

```

78 \def\textcolor#1#2{\@textcolor{#1}}
79 \def\@textcolor#1#2#3{\protect\leavevmode{\color#1{#2}#3}}

```

3.3 Background (Page) Colour

`\pagecolor` `\pagecolor`, which has the same argument forms as `\color`, specifies the background colour for the current, and all following, pages. It is a global declaration which does not respect \TeX groups.

```

80 \def\pagecolor{%
81   \begingroup
82     \let\ignorespaces\endgroup
83     \let\set@color\set@page@color
84     \color}

```

4 Defining Colours

`\definecolor` `\definecolor{name}{model}{colour-spec}` defines the color *name*, which may then be used in subsequent `\color` or `\textcolor` commands to refer to a colour specified by *colour-spec* in the colour model *model*.

`\definecolor` associates the *name* to a colour in *model*. So `\color{name}` would check *name* then issue a `\special` for the colour model *model*.

`\definecolor` just calls an internal macro that defines the colour for a particular model. This macro must have been defined by the driver file that supports the requested *model*.

```
85 \def\definecolor#1#2#3{%
86   \ifundefined{color@#2}%
87     {\color@error{model ' #2'}}%
88     {\ifundefined{\string\color @#1}{}%
89       {\PackageInfo{color}{Redefining color #1}}%
90       \csname color@#2\expandafter\endcsname
91         \csname\string\color @#1\endcsname{#3}}}
```

`\DefineNamedColor` Driver files may opt to define a ‘named’ colour model. Placing colour names rather than numeric specifications into the dvi file has certain advantages, in that post processing software can tune the colour specifications to the particular technology being used, and more easily make colour separations for that colour. The disadvantage is that the driver must ‘know’ the colour names.

The ‘color1’ drivers (dvips) currently ignore the specification of the colour, and once a name is defined, just put the colour name in the dvi file. For dvips, The header file `color.pro` is used to give the cmyk equivalents of the names.

The ‘color2’ drivers (textures) use a special postscript operator that takes both the name and the cmyk equivalent. so if the names are no being used, fall back’ definitions in the cmyk model are available. These drivers also allow a numeric value to affect the ‘density’ of the colour to use.

Drivers based on ‘color3’ do not support named colours at the dvi level, but to ease document portability, the named model is still defined, but the `\special`’s just put the colour specifications, not the names, into the dvi file.

Normally after a colour, say `JungleGreen`, has been declared with:

```
\DefineNamedColor{named}{JungleGreen}{cmyk}{1,2,3,4}
```

it is available in the ‘named’ colour model, for instance by

```
\color[named]{JungleGreen}
```

A user may give a more convenient name, using

```
\definecolor{mygreen}{named}{JungleGreen}
```

If however you are happy with the original names, and want to use them directly, as in `\color{JungleGreen}` without specifying `[named]` all the time, just give the package option `usenames`, which will redefine `\DefineNamedColor`, so that the colour name is declared as a user-colour as well as a name in the ‘named’ model.

```
92 \def\DefineNamedColor#1#2#3#4{%
93   \ifundefined{define@color@#1}%
94     {\color@error{model ' #1'}}%
95     {\ifundefined{color@#3}%
96       {\color@error{model ' #3'}}%
97       {\ifundefined{color@#1@#2}{}%
98         {\PackageInfo{color}{Redefining color #2 in named color model}}%
99       }}
```

```

99      \csname color@#3\endcsname\@tempa{#4}%
100     \csname define@color@#1\endcsname{#2}\@tempa
101     \c@lor@username{#2}}}}
102 \@onlypreamble\DefineNamedColor

```

5 Colour Switch

`\ifcolors@` This boolean can be tested by higher level macros that may want to alter their behaviour if a monochrome driver is being used.

```

103 \newif\ifcolors@
104 \colors@true

```

6 Whatsit...

`\c@lor@special` Some drivers can not support all the features of this package. They should always put a *whatsit* in the current list though. the following macro has most of the features of `\special`, but does not put anything into the dvi file. It does write to the log file or the terminal (depending on the value of #1).

```

105 \def\c@lor@special#1#2{%
106   \edef\@tempa{\write#1{#2}}\@tempa}

```

7 Processing Options

A local configuration file may declare more options. It should also make one driver option the default, by calling `\ExecuteOptions` with the appropriate option.

```

107 \InputIfFileExists{color.cfg}{-}{-}

```

After the options are processed, load the appropriate driver file. If a site wants a default driver (eg `dvips`) it just needs to put `\ExecuteOptions{dvips}` in a `color.cfg` file.

```

108 \ProcessOptions
109 \if!\Gin@driver!
110   \PackageError{color}
111     {No driver specified}
112     {You should make a default driver option in a file \MessageBreak
113       color.cfg\MessageBreak
114       eg: \protect\ExecuteOptions{dvips}%
115     }
116 \else
117   \PackageInfo{color}{Driver file: \Gin@driver}
118   \@ifundefined{ver@\Gin@driver}{\input{\Gin@driver}}{-}
119 \fi
120 \@ifundefined{c@lor@namefile}{-}{\input{\c@lor@namefile}}

```

8 Default Colour

`\normalcolor` Early versions of this package redefined `\reset@font` to reset the color as well. Current versions do not do this (there are too many `\reset@font` commands

hidden in strange places) and so defines a separate command, `\normalcolor` to reset the colour to the colour in effect at the start of the document.

`\normalcolor` is defined (to `\relax`) in the L^AT_EX kernel, so it is safe to use this in macros that may possibly be used in conjunction with colour. It will have no effect until the `color` package is also loaded.

```
121 \def\normalcolor{\let\current@color\default@color\set@color}
```

`\default@color` Internal macro to store the ‘default’ colour used by `\normalcolor`.

```
122 \AtBeginDocument{\let\default@color\current@color}
```

`\current@color` contains an internal representation of the colour at this point in the document. (This can only be an approximation to the truth as the ‘macro layer’ of T_EX does not know where the output routine is going to re-insert oas. This is why drivers must maintain their own stack of colours in order to fully support these commands.

For dvips, the `\current@color` it is something like ‘Black’ or ‘rgb 0 1 0’, but other packages should not rely on any particular format for this macro.

The driver file *must* initialise `\current@color` to a specification for Black. This initialisation can not occur here, as the possible colour models (and thus the syntax for ‘black’) are not known at this point.

9 Higher Level Commands

With the basic colour primitives specified above we may define a few higher level commands for coloured boxes etc. This is still quite a low level and presumably packages and classes making use of colour will define more appropriate document-level commands.

9.1 Colour Block

`\color@block` `\color@block{width}{height}{depth}`

Should take up no space for T_EX, but produce a block in the current colour of the specified size. It is mainly used for producing box backgrounds.

The definition here works by selecting a colour, and then drawing a T_EX rule (unless `\ifcolors@false`). This allows the ‘driver independent’ colour specials to be used. However it is defined using `\providecommand`, so that this file will not over-write any other definition of this command. A graphics package may want to define it using a special to produce (for example) a PostScript line. Producing the line in the `\special` has the advantage that on a preview that does not understand `\specials`, the line is automatically omitted, without needing to modify the source of the document (for instance by adding the `monochrome` option).

```
123 \def\color@block#1#2#3{%
```

```
124   {\set@color\rlap{\ifcolors@\vrule\@width#1\@height#2\@depth#3\fi}}}
```

9.2 Coloured Boxes

`\colorbox` `\colorbox` takes the same argument forms as `\textcolor`, but the colour specifies the *background* colour of the box.

```
125 \def\colorbox#1#{\color@box{#1}}
```

```

\color@box
126 \def\color@box#1#2{\color@b@x\relax{\color#1{#2}}}

\fcolorbox \fcolorbox has an extra colour-spec argument, and puts a frame of the first colour
around a box with a background specified by the second colour. If an optional
argument is given, it specifies the colour model for both colours.

\fcolorbox
127 \def\fcolorbox#1#2#3{\color@fbox{#1}}
128 \def\color@fbox#1#2#3{%
129   \color@b@x{\fboxsep\z@\color#1{#2}\fbox}{\color#1{#3}}}

\color@b@x Internal macro for \colorbox and \fcolorbox.
130 \long\def\color@b@x#1#2#3{%
131   \leavevmode
132   \setbox\z@\hbox{\kern\fboxsep{\set@color#3}\kern\fboxsep}%
133   \dimen@ \ht\z@\advance\dimen@\fboxsep\ht\z@\dimen@
134   \dimen@ \dp\z@\advance\dimen@\fboxsep\dp\z@\dimen@
135   {#1{#2\color@block{\wd\z@}{\ht\z@}{\dp\z@}%
136     \box\z@}}

```

10 Extra Groups

Turning on extra groups in the standard L^AT_EX commands, so that colour commands are scoped correctly.

Like `\normalcolor`, the following five commands are defined in the kernel, with empty definitions (`\relax`). This means that they can be used to make macros in packages ‘colour safe’. The commands will not have any effect unless a user also uses this colour package, when the ‘active definitions’ here will take effect and keep colour commands correctly scoped.

```

\color@setgroup This is to be used in contexts (eg ‘lrbox’) where text is to be saved and used
after some other, unknown, text that may contain colour commands. A matching
\color@endgroup should be used at the end of the text.
137 \def\color@setgroup{\begingroup\set@color}

\color@begingroup This is to be used at the start of contexts that may contain colour commands, but
where it is not necessary to save the current colour. Examples of this are in the box
commands of ltboxes.dtx where user-supplied text is saved internally in a box
between \color@begingroup, \color@endgroup, but the box is used before any
other colour commands could intervene. A matching \color@endgroup should be
used at the end of the text.
138 \let\color@begingroup\begingroup

\color@endgroup To be used to close the ‘group’ started by one of the above two commands. The
\endgraf in its definition is required in the case of groups of text in vertical ‘par’
mode, but doesn’t do any harm in horizontal ‘LR’ contexts.
139 \def\color@endgroup{\endgraf\endgroup}

\color@hbox To be used to open a ‘coloured hbox’
140 \def\color@hbox{\hbox\bgroup\color@begingroup}

```


`\color@vbox` To be used to open a ‘coloured hbox’
141 `\def\color@vbox{\vbox\bgroup\color@begingroup}`

`\color@endbox` To be used to close a ‘coloured hbox’
142 `\def\color@endbox{\color@endgroup\egroup}`

11 Predefining Colours

As long as the driver file has defined sufficient colour models, we define a few colours, just to get people started.

black Black and white ‘colours’.

white 143 `\ifx\color@gray\@undefined`
144 `\ifx\color@rgb\@undefined`
145 `\else`
146 `\definecolor{black}{rgb}{0,0,0}`
147 `\definecolor{white}{rgb}{1,1,1}`
148 `\fi`
149 `\else`
150 `\definecolor{black}{gray}{0}`
151 `\definecolor{white}{gray}{1}`
152 `\fi`

red Additive primaries.

green 153 `\ifx\color@rgb\@undefined\else`

blue 154 `\definecolor{red}{rgb}{1,0,0}`
155 `\definecolor{green}{rgb}{0,1,0}`
156 `\definecolor{blue}{rgb}{0,0,1}`
157 `\fi`

cyan Subtractive primaries.

magenta 158 `\ifx\color@cmyk\@undefined\else`

yellow 159 `\definecolor{cyan}{cmyk}{1,0,0,0}`
160 `\definecolor{magenta}{cmyk}{0,1,0,0}`
161 `\definecolor{yellow}{cmyk}{0,0,1,0}`
162 `\fi`

163 `\endpackage`

12 And Finally

Restore Catcodes

164 `\Gin@codes`
165 `\let\Gin@codes\relax`